

DD11

STRUCTURAL STEEL

STANDARD	EN 10111																																																																								
QUALITY	Pickled & Oiled																																																																								
IDENTIFICATION NUMBER	1.0332																																																																								
CLASSIFICATION	-																																																																								
TYPE	Unalloyed Steel																																																																								
ROLLING STATE	AR - Rolling blank																																																																								
BRIEF DESCRIPTION	Sheet plates with low carbon content made from hot rolled coils for cold forming. Suitable for the bending process. Maximum yield and breakage limits and minimum lengths guaranteed. Suitable for cold processing.																																																																								
APPLICATIONS	All types of applications that require good mechanical characteristics, high hardness, and moderate workability.																																																																								
STANDARD COIL STOCK RANGE	<table border="1"> <thead> <tr> <th>DD11</th> <th>1000</th> <th>1250</th> <th>1500</th> <th>1830</th> <th>2000</th> </tr> </thead> <tbody> <tr><td>1.5</td><td>•</td><td>•</td><td>•</td><td></td><td></td></tr> <tr><td>2</td><td>•</td><td>•</td><td>•</td><td>•</td><td></td></tr> <tr><td>2.5</td><td>•</td><td>•</td><td>•</td><td></td><td>•</td></tr> <tr><td>3</td><td>•</td><td>•</td><td>•</td><td></td><td>•</td></tr> <tr><td>4</td><td>•</td><td>•</td><td>•</td><td></td><td>•</td></tr> <tr><td>5</td><td>•</td><td>•</td><td>•</td><td></td><td>•</td></tr> <tr><td>6</td><td>•</td><td>•</td><td>•</td><td></td><td>•</td></tr> <tr><td>8</td><td></td><td>•</td><td>•</td><td></td><td></td></tr> <tr><td>10</td><td></td><td>•</td><td>•</td><td></td><td></td></tr> <tr><td>12</td><td></td><td></td><td>•</td><td></td><td></td></tr> <tr><td>15</td><td></td><td></td><td>•</td><td></td><td></td></tr> </tbody> </table>	DD11	1000	1250	1500	1830	2000	1.5	•	•	•			2	•	•	•	•		2.5	•	•	•		•	3	•	•	•		•	4	•	•	•		•	5	•	•	•		•	6	•	•	•		•	8		•	•			10		•	•			12			•			15			•		
DD11	1000	1250	1500	1830	2000																																																																				
1.5	•	•	•																																																																						
2	•	•	•	•																																																																					
2.5	•	•	•		•																																																																				
3	•	•	•		•																																																																				
4	•	•	•		•																																																																				
5	•	•	•		•																																																																				
6	•	•	•		•																																																																				
8		•	•																																																																						
10		•	•																																																																						
12			•																																																																						
15			•																																																																						
CHEMICAL COMPOSITION	<p>Regulatory standard</p> <table border="1"> <thead> <tr> <th>C (%)</th> <th>Si (%)</th> <th>Mn (%)</th> <th>P (%)</th> <th>S (%)</th> <th>Al (%)</th> <th>Nb (%)</th> <th>Ti (%)</th> <th>V (%)</th> <th>Mo (%)</th> <th>Cu (%)</th> </tr> </thead> <tbody> <tr> <td>≤ 0.120</td> <td></td> <td>≤ 0.60</td> <td>≤ 0.045</td> <td>≤ 0.045</td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> </tr> </tbody> </table> <table border="1"> <thead> <tr> <th>Cr (%)</th> <th>Ni (%)</th> <th>N (%)</th> <th>B (%)</th> <th>Nb+Ti+V (%)</th> <th>Cr+Mo+Ni (%)</th> <th>Ni+Cr+Cu+Mo (%)</th> <th>C.E.V. (%)</th> </tr> </thead> <tbody> <tr> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> </tr> </tbody> </table> <p>$C.E.V. (%) = C + (Mn/6) + [(Cr+Mo+V)/5] + [(Ni+Cu)/15]$</p>	C (%)	Si (%)	Mn (%)	P (%)	S (%)	Al (%)	Nb (%)	Ti (%)	V (%)	Mo (%)	Cu (%)	≤ 0.120		≤ 0.60	≤ 0.045	≤ 0.045							Cr (%)	Ni (%)	N (%)	B (%)	Nb+Ti+V (%)	Cr+Mo+Ni (%)	Ni+Cr+Cu+Mo (%)	C.E.V. (%)																																										
C (%)	Si (%)	Mn (%)	P (%)	S (%)	Al (%)	Nb (%)	Ti (%)	V (%)	Mo (%)	Cu (%)																																																															
≤ 0.120		≤ 0.60	≤ 0.045	≤ 0.045																																																																					
Cr (%)	Ni (%)	N (%)	B (%)	Nb+Ti+V (%)	Cr+Mo+Ni (%)	Ni+Cr+Cu+Mo (%)	C.E.V. (%)																																																																		
MECHANICAL PROPERTIES	<p>According to UNI EN 10111</p> <table border="1"> <thead> <tr> <th>Mechanical characteristics</th> <th>Direction</th> <th>Thicknesses</th> <th>Values</th> </tr> </thead> <tbody> <tr> <td rowspan="2">R_e (MPa)</td> <td rowspan="2">T</td> <td>≥ 1 < 2</td> <td>170-360</td> </tr> <tr> <td>≥ 2 ≤ 11</td> <td>170-340</td> </tr> <tr> <td>R_m (MPa)</td> <td>T</td> <td></td> <td>≤ 440</td> </tr> <tr> <td rowspan="3">A₃₀ (%)</td> <td rowspan="3">T</td> <td>≥ 1 < 1.5</td> <td>≥ 22</td> </tr> <tr> <td>≥ 1.5 < 2</td> <td>≥ 23</td> </tr> <tr> <td>≥ 2 < 3</td> <td>≥ 24</td> </tr> <tr> <td>A₅ (%)</td> <td>T</td> <td>≥ 3 ≤ 11</td> <td>≥ 28</td> </tr> <tr> <td>Bend Test 180°</td> <td></td> <td></td> <td></td> </tr> <tr> <td>KV 20°C (J)</td> <td></td> <td></td> <td></td> </tr> <tr> <td>KV 0°C (J)</td> <td></td> <td></td> <td></td> </tr> <tr> <td>KV -20°C (J)</td> <td></td> <td></td> <td></td> </tr> <tr> <td>KV -40°C (J)</td> <td></td> <td></td> <td></td> </tr> <tr> <td>KV -50°C (J)</td> <td></td> <td></td> <td></td> </tr> </tbody> </table> <p>* = Standard option t = thickness in mm of the test piece for the bend test</p> <p>L = Tensile testing carried out on longitudinal test pieces T = Bend tests carried out on cross-cut test pieces</p>	Mechanical characteristics	Direction	Thicknesses	Values	R _e (MPa)	T	≥ 1 < 2	170-360	≥ 2 ≤ 11	170-340	R _m (MPa)	T		≤ 440	A ₃₀ (%)	T	≥ 1 < 1.5	≥ 22	≥ 1.5 < 2	≥ 23	≥ 2 < 3	≥ 24	A ₅ (%)	T	≥ 3 ≤ 11	≥ 28	Bend Test 180°				KV 20°C (J)				KV 0°C (J)				KV -20°C (J)				KV -40°C (J)				KV -50°C (J)																									
Mechanical characteristics	Direction	Thicknesses	Values																																																																						
R _e (MPa)	T	≥ 1 < 2	170-360																																																																						
		≥ 2 ≤ 11	170-340																																																																						
R _m (MPa)	T		≤ 440																																																																						
A ₃₀ (%)	T	≥ 1 < 1.5	≥ 22																																																																						
		≥ 1.5 < 2	≥ 23																																																																						
		≥ 2 < 3	≥ 24																																																																						
A ₅ (%)	T	≥ 3 ≤ 11	≥ 28																																																																						
Bend Test 180°																																																																									
KV 20°C (J)																																																																									
KV 0°C (J)																																																																									
KV -20°C (J)																																																																									
KV -40°C (J)																																																																									
KV -50°C (J)																																																																									
TOLERANCES	<p>Tolerances on the dimensions and on the shape UNI EN 10051 Surface condition UNI EN 10163-2</p>																																																																								
CERTIFICATIONS	EN10204-2.2 or higher																																																																								